


ATTORNEY DOCKET NO. 08146.0005U1
International Application No. PCT/EP2003/008347

Remarks

The specification is amended herein to update the priority claim for this application and to include the abstract as a separate sheet in accordance with 37 CFR 1.72. The claims have been amended to delete instances of multiple dependencies. No new matter is believed to be added.

Respectfully submitted,

NEEDLE & ROSENBERG, P.C.




Lawrence A. Villanueva
Registration No. 43,968

NEEDLE & ROSENBERG, P.C.
Customer Number 23859
(678) 420-9300
(678) 420-9301 (fax)

CERTIFICATE OF EXPRESS MAILING UNDER 37 C.F.R. § 1.10

I hereby certify that this correspondence, including any items indicated as attached or included, is being deposited with the United States Postal Service as Express Mail, Label No. EL980234284US, in an envelope addressed to: Mail Stop PCT, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450, on the date indicated below.



Scott Darnell

Date

ABSTRACT

The invention relates to a process for the chromatographic separation of components (19, 20, 25, 26, 28, 29) of a multiple-component fluid mixture (2a) by means of the Simulated Moving Bed process, in which the multiple-component fluid mixture (2a) and at least one solvent (3a) are passed into a plurality of at least one chamber (10a – 10c; 11a – 11c; 12a – 12c; 13a – 13c) or chamber sections containing a solid, at a first and second input (9b, 9d; 9f, 9h), and an extract flow (6a), which contains at least one first component (19, 26, 29) separated from the multiple-component fluid mixture (2a), as well as a raffinate flow (7a), which contains at least one second component (20, 25, 28) separated from the multiple-component fluid mixture (2a) are drawn off from the chambers (10a – 10c; 11a – 11c; 12a – 12c; 13a - 13c) or chamber sections at a first and second outlet (9a, 9c; 9e, 9g), whereby the chambers (10a – 10c; 11a – 11c; 12a – 12c; 13a - 13c) or chamber sections forming a closed circuit (8a, 8b; 18) are connected together in series, whereby the concentration of the input multiple-component fluid mixture (2a) and/or a composition of the solvent (3a) is/are changed within the cycle unit.